ThinkCentre M710 Tiny Platform Specifications

Processor	Intel® Celeron®, Intel Pentium®, or 6/7th Generation Intel Core™ i3 / i5 / i7 Processor						Security features				
	Processor Cores / Frequency Base/Max(GHz) Cache Memory Support Integrated Graphics					Integrated Graphics	Kensington® MicroSaver® cable) • Hard disk password • Smart USB protection, allows keyboard/ • Boot sequence control				
	Pentium G4400T	2/2	2.9G	3 MB	DDR4-2133	HD 510		mouse only, blocks all storage devices • Power-on password • Boot without keyboard and mouse • Individual USB port disablement • Chassis intrusion switch Some: Lenovo Calliope Keyboard (USB connector), black			
	Pentium G4560T	2/4	2.9G	3 MB	DDR4-2400	HD 610					
	Pentium G4600T	2/4	3.0G	3 MB	DDR4-2400	HD 630	Keyboard				
	Core i3-6100T	2/4	3.2G	3 MB	DDR4-2133	HD 530	Mouse	Some: Lenovo Traditional Keyboard (USB connector), black Some: Lenovo Calliope Wireless Keyboard (2.4GHz via USB receiver), black Some: Lenovo Calliope Mouse (USB connector), black Some: Lenovo Calliope Wireless Mouse (2.4GHz via USB receiver), black Tiny (1L), black color; metal case • Toolless chanssis open • Toolless HDD, SSD, memory removal • Optional toolless chanssis screw • Optional dust filter			
	Core i5-6500T	4/4	2.5G / 3.1G	6 MB	DDR4-2133	HD 530					
	Core i7-6700T	4/8	2.8G / 3.6G	8 MB	DDR4-2133	HD 530					
	Core i3-7100T	2/4	3.4G	3 MB	DDR4-2400	HD 630					
	Core i5-7400T	4/4	2.4G / 3.0G	6 MB	DDR4-2400	HD 630	Mechanical				
	Core i5-7500T	4/4	2.7G / 3.3G	6 MB	DDR4-2400	HD 630					
	Core i5-7600T	4/4	2.8G / 3.7G	6 MB	DDR4-2400	HD 630					
	Core i7-7700T	4/8	2.9G / 3.8G	8 MB	DDR4-2400	HD 630					
Memory	32GB max, DDR4-2400*, two 260-pin SO-DIMM sockets, non-ECC, dual-channel capable * System automatically clocks down for the processors with lower memory controller						r		Dimensions (WxDxH)	Weight (Approx.)	
								M710 Tiny only	7.05" X 7.20" X 1.36" 179mm X 182.9mm X 34.5mm	2.91 lb (1.32 kg), vary by config	
Storage	Some: Hard Drive / SATA 6.0Gb/s, 2.5", 5400 rpm or 7200 rpm Some: Solid State Drive (SSD) / SATA 6.0Gb/s, 2.5" Some: M.2 Solid State Drive (SSD) / PCIe NVMe, PCIe 3.0 x 4, 32Gb/s Some: Intel Optane™ Memory Ready (models with 7th gen Core processor), M.2 Some: DVD-ROM, slim (9.0mm), via USB external ODD box Some: DVD Burner (DVD±RW), slim (9.0mm), via USB external ODD box One onboard SATA 6.0Gb/s connector None							With VESA mount & ODD box	7.42" X 7.30" X 2.48" 188.4mm X 185.38mm X 63mm	3.66 lb (1.66 kg), vary by config	
Optical								With VESA mount & I/O box	7.42" X 7.30" X 2.62" 188.4mm X 185.38mm X 66.6mm	3.66 lb (1.66 kg), vary by config	
Onboard SATA Media reader							VESA mount Floor Stand	Optional VESA mount bracket kit, supports VESA 75mm and 100mm Optional system floor stand for vertical orientation			
Graphics	Intel HD Graphics 510/530/610/630 in processor, uses main memory, DirectX [®] 12, two DisplayPort™, one optional video port (HDMI, VGA, 3rd DP, or USB 3.1 Type-C with DisplayPort Alternate Mode), up to 3 independent displays; Max resolution: 4096x2304 (DP) @ 60Hz; 4096x2304 (Type-C) @ 60Hz;						Power supply	65 watts AC/DC adapter, autosensing, 88% PSU (not included for TIO models) 90 watts AC/DC adapter, autosensing, 88% PSU (only for models with I/O box)			
							Limited warranty ³ Some: 1-year or 3-year, depot service / service upgrades available Some: 1-year or 3-year, limited onsite service / service upgrades available				
Monitor cable	Optional Dr to VGA, Dr to DVI-D (single link), Dr to dual Dr, of Dr to HDIVII 1.4						Preload Some: Windows® 7 Professional 32/64 preinstalled through downgrade				
Chipset	Intel B250 Chipset							rights in Windows 10 Pro 64-bit (not available with 7th Gen Intel processor) Some: Windows 10 Pro 64-bit Some: Windows 10 Home 64-bit Preloaded applications (only some listed) Microsoft Office preloaded; purchase a product key to activate Cyberlink PowerDVD Create (DVD±RW) Only for Window 10			
Front ports	Two USB 3.1 Gen1 (one is Always On and fast charge), one microphone (3.5mm),										
Rear ports	one headphone / microphone combo jack (3.5mm) Four USB 3.1 Gen1 (optional external optical box or external I/O box occupies one or two specific USB 3.1 Gen1 on some models), ethernet (RJ-45), two DisplayPort, two optional ports (Port 1 for VGA / 3rd DP / HDMI / serial / USB 3.1 Type-C Gen 1 (with DisplayPort Alternate Mode), Port 2 for serial) Optional external I/O box, extends two USB 2.0, two USB 3.1 Gen1, and one serial on rear, two USB 2.0 on front, via USB cable (occupy two specific USB 3.1 Gen1 of Tiny)										
I/O box											
Audio support	High Definition (HD) Audio, Realtek ALC294 / optional internal speaker (1w or 2w)						1				
WLAN ¹³	Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA9377A (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Qualcomm Atheros QCA6174A (dual band), Wi-Fi + Bluetooth 4.1 combo adapter, 2x2 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 3165, Wi-Fi + Bluetooth 4.1 combo adapter, 1x1 Some: 11ac wireless, M.2 Card, Intel Dual Band Wireless-AC 8265, Wi-Fi + Bluetooth 4.1 combo adapter, 2x2 Some: Bluetooth 4.1 wireless, integrated in Wi-Fi + BT combo adapter Gigabit ethernet, Intel Ethernet Connection I219-V (Jacksonville), Wake on LAN® None						1	 Lenovo Companio 			
								 Lenovo ID Cyberlink PowerDVD (DVD, DVD±RW) Only for Window 7 			
									Lenovo Solution Center		
								Lenovo ThinkVantage Tools Create Recovery Media Adobe® Reader®			
							Environment	ENERGY STAR® 6.1, EPEAT™ Gold rating (North America), ErP Lot 3, GREENGUARD®, RoHS-compliant, TUV low noise verified (on some models)			
Bluetooth™ Ethernet Modem	Gigabit ethernet, In	ntel Ether	net Connection I	219-V (Ja	acksonvine), wak	CONLAN					
Ethernet	Gigabit ethernet, In	form Mod	ule) 2.0*, TCG Co	ertified		e on LAN	MIL-SPEC test	TUV low noise verified MIL-STD-810G milita	ed (on some models) ary certification (Low Pressure [Altitu mperature Shock, Humidity, Sand a	nde], High Temperature, nd Dust, Vibration, Shoo	

See footnotes for more detailed information